



## SSCP5401GS7

### PNP Switching Transistor

#### ➤ Features

VCB	VCE	VEB	IC
-160V	-150V	-6V	-600mA

#### ➤ Description

This device is designed for general-purpose high-voltage amplifiers and gas discharge display drivers. It is Ideal for medium power amplification and switching.


#### ➤ Applications

- General-purpose high-voltage amplifiers
- Gas discharge display drivers
- Medium power amplification and switching


#### ➤ Ordering Information

Device	Package	Shipping
SSCP5401GS7	SOT-323	3000/Reel


#### ➤ Pin configuration



**SOT-323**



**Circuit Diagram**



**Marking(Top View)**



➤ **Absolute Maximum Ratings**( $T_A=25^{\circ}\text{C}$  unless otherwise noted)


Parameter	Symbol	Value	Unit
Collector-Base Voltage	$V_{CB0}$	-160	V
Collector- Emitter Voltage	$V_{CE0}$	-150	V
Emitter-Base Voltage	$V_{EBO}$	-5	V
Collector Current-Continuous	$I_C$	-600	mA
Collector Power Dissipation	$P_C$	200	mW
Junction Temperature	$T_J$	-55 to 150	$^{\circ}\text{C}$
Storage Temperature	$T_{STG}$	-55 to 150	$^{\circ}\text{C}$

➤ **Electrical Characteristics** ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$BV_{CB0}$	$I_C=-100\mu\text{A}, I_E=0$	-160			V
Collector-emitter Breakdown Voltage	$BV_{CE0}$	$I_C=-1\text{mA}, I_B=0$	-150			V
Emitter -Base Breakdown Voltage	$BV_{EBO}$	$I_E=-100\mu\text{A}, I_C=0$	-5			V
Collector Cutoff Current	$I_{CB0}$	$V_{CB}=-120\text{V}, I_E=0$			-50	nA
Emitter Cutoff Current	$I_{EBO}$	$V_{EB}=-4, I_C=0$			-50	nA
DC Current Gain	$h_{FE1}$	$V_{CE}=-5\text{V}, I_C=-1\text{mA}$	50			
	$h_{FE2}$	$V_{CE}=-5\text{V}, I_C=-10\text{mA}$	100		300	
	$h_{FE3}$	$V_{CE}=-5\text{V}, I_C=-50\text{mA}$	50			
Collector-Emitter Saturation Voltage	$V_{CE(sat)1}$	$I_C=-50\text{mA}, I_B=-5\text{mA}$			-0.5	V
	$V_{CE(sat)2}$	$I_C=-10\text{mA}, I_B=-1\text{mA}$			-0.2	V
Base-Emitter Saturation Voltage	$V_{BE(sat)1}$	$I_C=-50\text{mA}, I_B=-5\text{mA}$			-1.0	V
	$V_{BE(sat)2}$	$I_C=-10\text{mA}, I_B=-1\text{mA}$			-1.0	V
Collector output capacitance	$C_{ob}$	$V_{CB}=-10\text{V}, I_E=0, f=1\text{MHz}$			6	pF
Transition frequency	$f_T$	$V_{CE}=-5\text{V}, I_C=-10\text{mA}$ $f=30\text{MHz}$	100		300	MHz




➤ **Typical Performance Characteristics ( $T_A=25^\circ\text{C}$  unless otherwise noted)**




**Collector Current vs. Base-Emitter Voltage**




**DC Current Gain vs. Collector Current**




**$V_{BE(sat)}$  vs. Collector Current**



**$V_{CE(sat)}$  vs. Collector Current**






**Power derating vs. Ambient temperature**



**Transition Frequency vs. Collector Current**

## Package Information

SOT-323



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	2.150	2.450	0.085	0.096
E1	1.150	1.350	0.045	0.053
e	0.650 TYP.		0.026 TYP.	
e1	1.200	1.400	0.047	0.055
L	0.260	0.460	0.010	0.018
L1	0.525 REF.		0.021 REF.	
$\theta$	0°	8°	0°	8°



## DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.